



## Classic Sizing Tool

PV Module Data			
Power	214	Watts	
VOC	35.8	Volts	
VMP	29.6	Volts	
ISC	7.68	Amps	
IMP	7.24	Amps	
VOC Temp Coef %	0.3	C	
VMP Temp Coef %	0.36	Amps	
Environmental Data			
Coldest Ambient Temperature	50	F	
Hottest Ambient Temperature	104	F	
Nominal Battery Volts	24	Volts	
PV Array			
Number Of Modules In Series	3		
Number Of Parallel Strings	4		
Total Modules	12		
Rated PV Array Power	2568	Watts	
Anticipated Array Power @ 104 F	2429	Watts	
Rated PV Array Current	28.96	Amps	
Battery Charging Current @ 28.8V	89.2	Amps	
VMP (Maximum Power Point Voltage)	88.8	Volts	
VOC (Open Circuit Voltage)	107.4	Volts	
VMP @ 50 F	93.6	Volts	
VOC @ 50 F	112.2	Volts	
Charge Controllers			
	CLASSIC 150/LITE	CLASSIC 200/LITE	CLASSIC 250/LITE
Max Operating Voltage	150	200	250
Max None Operating VOC (HyperVOC) @ 48V Nominal Bat Voltage	174	224	274
Maximum Number Of Modules In Series Configuration	4	5	6
Max Number Of Modules In Series Using HyperVOC	4	5	7
Max Allowable Output Current Per Classic Based On This Current	94	74	62
Max Allowable Wattage Per Classic Based On This Configuration	2700	2123	1779
Present PV Array Wattage Of This Configuration	2568	2568	2568
Design Check			
Max VOC	OK	OK	OK
Temp The Classic Enters HyperVOC	-160.6 F°	-439.6 F°	-720.4 F°
Array Power (Wattage)	OK	EXCESSIVE	EXCESSIVE
Classics Required	1	1.3	1.5

NOTE: MidNite Solar recommends a second controller be added after 1.2

WARNING: MidNite Solar makes no representation, warranty or assumption of liability regarding the use of the String Calculator. This tool uses data provided by other parties (such as PV module specs) and makes calculations based on assumptions which may or may not prove to be valid.