

CLASSIC SIZING TOOL

PV Module Data

Power:	320	Watts
VOC (Open Circuit Voltage):	45.83	Volts
VMP (Maximum Power Point Voltage):	36.91	Volts
ISC: (Short Circuit Amperage)	9.15	Amps
IMP (Maximum Power Point Amperage):	8.67	Amps
VOC Temp Coef %:	0.34	C°
VMP Temp Coef %:	0.41	C°

Environmental Data

Coldest Ambient Temperature:	-15	C°
Hottest Ambient Temperature:	40	C°
Nominal Battery Volts:	24	Volts

PV Array

Number Of Modules In Series:	2
Number Of Parallel Strings:	3
Total Modules	6
Rated PV Array Power:	1920 Watts
Anticipated Array Power @ 35C:	1841 Watts
Rated PV Array Current:	26.01 Amps
Battery Charging Current @ 28.8 V:	66.7 Amps
VMP (Maximum Power Point Voltage) :	73.82 Volts
VOC (Open Circuit Voltage):	91.66 Volts
VMP @ -15 C°:	86 Volts
VOC @ -15 C°:	104.2 Volts

Charge Controller Selection

Classic150/Lite Classic200/Lite Classic250/Lite

Max Operating Voltage	150	200	250
Max Non operating VOC (HyperVOC) @ 24V Nominal Battery Voltage	174	224	274
Maximum Number Of Modules In Series	2	3	4
Max Number Of Modules In Series (Using HyperVOC)	3	4	5
Max Allowable Output Current Per Classic Based On This Current Configuration	94	74	62
Max Allowable Wattage Per Classic Based On This Current Configuration	2700	2123	1779
Present PV Array Wattage Of This Configuration	1920	1920	1920

Design Check

Max VOC	OK	OK	OK
Temperature The Classic Will Enter HyperVOC	-162 C°	-323 C°	-483 C°
Array Power (Wattage)	OK	OK	EXCESSIVE
Classics Required	0.8	1	1.1

NOTE: MidNite Solar recommends a second controller be added after 1.2

WARNING: MidNite Solar makes no representation, warranty or assumption of liability regarding the use of the String Calculator. This tool uses data provided by other parties (such as PV module specs) and makes calculations based on assumptions which may or may not prove to be valid.

[Create PDF](#)

MidNite Solar Inc.
17722 - 67th Ave NE,
Arlington, WA 98223
Ph. 360-403-7207
Fax 360-691-6862
www.midnitesolar.com