



Classic Sizing Tool

PV Module Data			
Power	320	Watts	
VOC	46.28	Volts	
VMP	37.16	Volts	
ISC	8.92	Amps	
IMP	8.61	Amps	
VOC Temp Coef %	0.33	C	
VMP Temp Coef %	0.45	Amps	
Environmental Data			
Coldest Ambient Temperature	-10	C	
Hottest Ambient Temperature	40	C	
Nominal Battery Volts	24	Volts	
PV Array			
Number Of Modules In Series	3		
Number Of Parallel Strings	3		
Total Modules	9		
Rated PV Array Power	2880	Watts	
Anticipated Array Power @ 40 C	2686	Watts	
Rated PV Array Current	25.83	Amps	
Battery Charging Current @ 28.8V	100	Amps	
VMP (Maximum Power Point Voltage)	111.4	Volts	
VOC (Open Circuit Voltage)	138.8	Volts	
VMP @ -10 C	129	Volts	
VOC @ -10 C	154.8	Volts	
Charge Controllers			
	CLASSIC 150/LITE	CLASSIC 200/LITE	CLASSIC 250/LITE
Max Operating Voltage	150	200	250
Max None Operating VOC (HyperVOC) @ 48V Nominal Bat Voltage	174	224	274
Maximum Number Of Modules In Series Configuration	2	3	4
Max Number Of Modules In Series Using HyperVOC	3	4	5
Max Allowable Output Current Per Classic Based On This Current	82	74	62
Max Allowable Wattage Per Classic Based On This Configuration	2353	2123	1779
Present PV Array Wattage Of This Configuration	2880	2880	2880
Design Check			
Max VOC	MARGINAL (HyperVOC)	OK	OK
Temp The Classic Enters HyperVOC	1 C°	-108 C°	-218 C°
Array Power (Wattage)	EXCESSIVE	EXCESSIVE	EXCESSIVE
Classics Required	1.3	1.4	1.7

NOTE: MidNite Solar recommends a second controller be added after 1.2

WARNING: MidNite Solar makes no representation, warranty or assumption of liability regarding the use of the String Calculator. This tool uses data provided by other parties (such as PV module specs) and makes calculations based on assumptions which may or may not prove to be valid.